

MWC FRONT LOAD CONTAINER SPECIFICATIONS							
	1 1/2 YD	2 YD	3 YD	4 YD	6 YD	8 YD Slant Top	8 YD Box Type
TOP WIDTH	72"	72"	72"	72"	72"	72"	72"
BOTTOM WIDTH	69"	69"	69"	69"	67 1/2"	67"	67"
SIDES (ga.)	14 ga.	14 ga.	12 ga.	12 ga.	12 ga.	12 ga.	10 ga.
BOTTOM(ga.)	14 ga.	14 ga.	12 ga.	12 ga.	10 ga.	10 ga.	10 ga.
TOP DEPTH	30"	37"	44 1/2"	54	75"	92"	77-1/8"
BOTTOM DEPTH	26"	33"	37 1/2"	48"	70"	85"	72"
FRONT HEIGHT	36"	37 1/2"	42 1/2"	44"	48"	50"	72-1/2"
BACK HEIGHT	36"	39 1/2"	58 1/2"	58 1/2"	62"	71"	72-1/2"
NO. LIDS	2	2	2	2	4	4	2
NO. SIDE DOORS 30" x 30"							2
Bolt-on Lift Pockets: Length 24"      Height 9 1/2"      Width 5" Length including Blunnderbuss 28 1/2" Material: 3/16" Bumper Pads, Lift Pockets, & Gussets - 3/8" Pocket Guides Bumper Pad Radius - 1" No. of fastening bolts: 11      Size: 1/2"							
Selling Points							
1. All sizes stackable.							
2. Lift pockets / Bumper Plate - 3/16"; Guides 3/8"							
3. Bolt-on lift pockets for ease of replacement and for container stackability.							
4. Square/rectangular tubing top frame for better container structural integrity and increased life.							
5. 100% inside body welding. - Longer container life.							
6. Painted to customer specifications.							